

MODEL: SA 20 & SA 30 TRANSFER



THE ULTIMATE SWINGING DRIVE-OVER TRANSFER CONVEYOR SPECIFICATIONS

Performance	SA 20	SA 30
Capacity (bushels per hour)	13,000	20,000
GPM (gallons per minute) at 2000 PSI	20	25
Dimensions		
Belt Width	20"	30"
Belt Length	48'	48'
Conveyor length	27'	27'
Spout Discharge Height	33"	26"
Total Weight	1460 lbs	2480 lbs
Tire Size	18.5 X10"	20.5 X10"
Drive-over frame Height	2.5"	2.5"
Drive-over frame Width	10.5'	10.5'
(Optional) Drive-over Frame	1' EXT	1' EXT
Adjustable Hopper	36 x 128	46 x 128
Features		
Drive-over Frame	Low Profile	Low Profile
Anti- Accident Safety Shut-off Feature	Standard	Standard
Self Cleaning Rollers	Standard	Standard
Swinging Drive Wheel	Standard	Standard
Adjustable Hitch	Standard	Standard
Adjustable Frame	Standard	Standard
Adjustable Belt Tension		
Extra Options		
Hydraulic Drive	Standard	Standard
Electric Drive	Optional	Optional
Gas Powered Drive	Optional	Optional

FEATURES:

- SAFETY SHUT OFF
- ULTIMATE LOW PROFILE OF ONLY 2.5" INCHES
- OIL SEED PRODUCT FRIENDLY (CANOLA)
- EASY TRANSPORT BY VEHICLE OR ATV
- SELF CLEANING ROLLERS
- SWING HOPPER TO HOPPER
- SELF CLEANING ROLLERS



AUTO SAFETY SHUT OFF

